



2. ELECTRICAL SPECIFICATIONS

Accuracy is calculated as \pm [% readings + (no. of digits) * resolution] at 23 °C \pm 5 °C, relative humidity <80%RH

DC Voltage

Range (V)	Resolution (V)	Accuracy
3 ÷ 1500	1	\pm (1.0%rdg + 2dgt)

AC TRMS Voltage

Range (V)	Resolution (V)	Accuracy
3 ÷ 1000	1	\pm (1.0%rdg + 3dgt)

Frequency range: 42.5 ÷ 69Hz ; Voltage zeroed for measured values <3V

Insulation Resistance (M Ω) – DUAL Mode

Test voltage DC [V]	Range [M Ω]	Resolution [M Ω]	Accuracy (*)
250, 500, 1000, 1500	0.1 ÷ 0.99	0.01	\pm (5%rdg + 5dgt)
	1.0 ÷ 19.9	0.1	
	20 ÷ 100	1	

(*) Accuracy indicated for VPN \geq 240V, R_{fault} \geq 10 Ω . Accuracy of Rp and R(+) not declared if R(+) \geq 0.2M Ω and R(-) <0.2M Ω Accuracy of Rp and R(-) not declared if R(+) < 0.2M Ω and R(-) \geq 0.2M Ω

Open voltage	<1.25 x nominal test voltage
Short circuit current	<15mA (peak) for each test voltage
Nominal measured current	>1mA on R = 1k Ω x V _{nom} (with VPN, VPE, VNE= 0)

Insulation Resistance (M Ω) –TIMER Mode

Test voltage DC [V]	Range [M Ω]	Resolution [M Ω]	Accuracy
250, 500, 1000, 1500	0.01 ÷ 9.99	0.01	\pm (5.0%rdg+ 5dgt)
	10.0 ÷ 99.9	0.1	

Open voltage	<1.25 x nominal test voltage
Short circuit current	<15mA (peak) for each test voltage
Nominal measured current	>1mA on R = 1k Ω x V _{nom} (with VPN, VPE, VNE= 0)
Setting timer:	3s ÷ 999s

Continuity of protection conductors (RPE)

Range [Ω]	Resolution [Ω]	Accuracy
0.00 ÷ 9.99	0.01	\pm (2%rdg + 2dgt)
10.0 ÷ 99.9	0.1	
100 ÷ 1999	1	

Test current:	>200mA DC up to 5 Ω (included cables), Resolution 1mA, Accuracy \pm (5.0%rdg + 5dgt)
Open voltage	4 < V _o < 10V

GFL (Ground Fault Locator) function

Test voltage DC [V]	Range [M Ω]	Resolution [M Ω]	Accuracy (*)	Position accuracy
250, 500, 1000, 1500	0.1 ÷ 0.99	0.01	\pm (5%rdg + 5dgt)	\pm 1module
	1.0 ÷ 19.9	0.1		
	20 ÷ 100	1		

(*)Accuracy indicated for VPN \geq 240V, R_{fault} \geq 10 Ω . Accuracy of Rp and R(+) not declared if R(+) \geq 0.2M Ω and R(-) <0.2M Ω Accuracy of Rp and R(-) not declared if R(+) < 0.2M Ω and R(-) \geq 0.2M Ω

Open voltage	<1.25 x nominal test voltage
Short circuit current	<15mA (peak) for each test voltage
Nominal measured current	>1mA on R = 1k Ω x V _{nom} (with VPN, VPE, VNE= 0)

The GFL function allows obtaining correct results with the following conditions:

- > Test carried out with V_{test} \geq V_{nom} on a single string disconnected from the inverter, from possible arresters and from earth connections
- > Test performed upstream of any blocking diodes
- > Single fault of low insulation located at any position in the string
- > Insulation resistance of the single fault <0.1M Ω
- > Environmental conditions similar to those in which the fault was reported



2. GENERAL SPECIFICATIONS

DISPLAY AND MEMORY:

Features: graphic COG 128x128pxl with backlight
Memory: max 999 test

POWER SUPPLY:

Battery type: 6x1.5V alkaline batteries type AA LR06 or
6x1.1V rechargeable batteries type AA LR06
Battery life: approx. 500 tests (for each functions)
Auto Power OFF: after 5 minutes o idleness

OUTPUT INTERFACE

PC communication port: optical/USB

MECHANICAL SPECIFICATIONS

Dimensions (L x W x H): 235 x 165 x 75mm
Weight (batteries included): 1.2kg
Mechanical protection: IP40

ENVIRONMENTAL CONDITIONS:

Reference temperature: 23°C ± 5°C
Working temperature: 0°C ÷ 40°C
Working humidity: <80%RH
Storage temperature: -10°C ÷ 60°C
Storage humidity: <80%RH
Max height of use: 2000m

REFERENCE GUIDELINES:

Instrument's safety: IEC/EN61010-1, IEC/EN61010-2-030
IEC/EN61010-2-033, IEC/EN61010-2-034
EMC: IEC/EN61326-1
Safety of measurement accessories: IEC/EN61010-031
General: IEC/EN62446
Measurement MΩ IEC/EN 61557-2
Measurement RPE: IEC/EN 61557-4
Insulation: double insulation
Pollution degree: 2
Overvoltage category: CAT III 1500V DC, CAT III 1000V AC
Max 1500V DC, 1000VAC between inputs

This instrument complies with the requirements of the European Low Voltage Directives 2014/35/EU (LVD) and EMC 2014/30/EU

This instrument satisfies the requirements of 2011/65/EU (RoHS) directive and 2012/19/EU (WEEE) directive